

# FC 510 tandem



## DATI TECNICI

Pompa a vuoto:	bagno d'olio - 60 mc/h
Dimensioni:	mm 1510x700x1050h
Dimensioni camera:	2x mm 650x535x200h
Tensione:	389/440 V - 50/60 Hz
Peso:	kg 280

## TECHNICAL DATA

Vacuum pump:	oil-lubricated - 60 mc/h
Size:	mm 1510x700x1050h
Chamber size	2x mm 650x535x200h
Power grid voltage:	389/440 V - 50/60 Hz
Weight:	kg 280

## DONNEES TECHNIQUES

Pompe a vide:	à bain d'huile - 60 mc/h
Dimensions:	mm 1510x700x1050h
Dimensions chambre:	2x mm 650x535x200h
Voltage:	389/440 V - 50/60 Hz
Poids:	kg 280

## DATOS TECNICOS

Bomba vacío:	aceite - 60 mc/h
Medidas:	mm 1510x700x1050h
Medidas de la cámara:	2x mm 650x535x200h
Tensión:	389/440 V - 50/60 Hz
Peso:	kg 280

## BARRA SALDANTE - SEALING BEAM

2x620 mm - 4x620 mm - 4x505 mm

## OPTIONALS - OPTIONALS - OPTIONS - OPCIONES

### DESCRIZIONE

Gas - Gas - Gaz - Entrada de gas inerte

Sensore di vuoto - Sensor - Capteur de vide - Sensor

Softair - Softair - Softair - Softair

Taglio sfrido - Cut of seal - Coupe sachets - Recorte sobrante de bolsa

Barra opzionale - Double beam - Double barre de soudure - Barra de soldadura extra